

DURABLE



SMALL, DURABLE AND EASY TO CONNECT

Increase productivity and reduce data errors in mobile business applications with the Socket Bluetooth Cordless Hand Scanner (CHS), a wireless barcode reader for smartphones and tablets that's small, portable and provides fast, industrial-class scanning performance.

- **Designed for Mobility** - Small, light, and portable with up to 14-hours battery life
- **Comfortable** - Ergonomic for comfortable use over extended periods
- **Easy to Connect** - Simply scan a barcode on the screen to quickly pair devices

CHS 7Di and 7DiRx

Ideal for field sales and field service, the CHS 7Di and 7DiRx is durable to withstand multiple drops to concrete, with a protective rubber bumper and rubber sealings.

CHS 7Pi

For special lighting conditions or barcode requirements featuring a Class 2 laser, the CHS 7Pi work well in bright sunlight, in low light, as well as with barcodes that are small, tightly spaced, on shiny surfaces or behind plastic or glass.

CHS 7Xi and 7XiRx

High performance for scanning 1D and 2D barcodes, printed or onscreen. Reads barcodes displayed on screen of smartphone, laptop, tablet, etc. Durable for outdoor use or fast, demanding operations.

Hardware Features

- Easily connect to Bluetooth® enabled smartphones, tablets, PDAs, notebooks and desktop computers:
 - Apple® iOS
 - Android®
 - Windows® 10, 8, 7, Vista, XP
 - Windows® Embedded Handheld (Windows Mobile)
 - Mac OS
- Made with antimicrobial plastics to provide an extra layer of protection to the device against the spread of potentially harmful microbes
- Battery Friendly® technology enables up to 14-hour battery life on a single charge
- Apple iOS certified to add support for Bluetooth SPP connections with iPad®, iPhone®, iPod touch® (Requires SDK or compatible app developed with SDK)
- Durable exterior casing withstand multiple 6.6 ft (2m) drops to concrete.
- Made with antimicrobial plastics to provide an extra layer of protection to the device against the spread of potentially harmful microbes
- Easy to use with automatic reconnections
- LED and beeps indicate good scan, connection, and power status
- Vibrate mode for good scans, great for noisy worksites where beeps are hard to hear or noise-sensitive applications where beeps must be disabled
- Quickly access Apple iOS on-screen keyboard with special "double press" scanner button feature
- Supports Bluetooth HID connections for easy setup with no software installation¹ (when in HID mode)
- Supports Bluetooth SPP connections for advanced scanner control²

Software Features (SPP mode only)

- SocketScan™ 10 keyboard wedge software enters scanned data into any application -- no custom programming needed
- Socket EZ Pair automates Bluetooth setup for maximum ease of use
- Suffix support: automatically add a carriage return or tab after each scan of data
- Software utility enables you to configure beep, LED and vibrate settings, enable / disable symbology (barcode type) and monitor scanner battery level
- Determine the symbology or length of a barcode
- SocketScan 10 SDK available with subscription to Socket Mobile Developer Program (\$19.95 / year) developer.socketmobile.com

¹HID not supported for BlackBerry OS or iPhone 3G

²SPP not supported for Mac OS or QNX. For iOS support with Bluetooth SPP, the SDK or a compatible app is required.

CHS Model	7Di	7DiRx	7Pi	7Xi	7XiRx
Scanner SKU #	Gray: CX2877-1472	White CX2879-1474	Gray: CX2874-1413	Gray: CX2864-1336	White CX2866-1338
Dimensions / Total Mass	5.2 X 1.77 X 1.49 in. (132 x 45.1 x 37.9 mm) / Total Mass: approx. 3.2 oz (90.7 g)				
Drop Specification	Durable exterior case withstands multiple 6.6 ft (2 m) drops to concrete				
Temperature	Operating Temperature: +32 to +122°F (0 to + 50°C) Storage Temperature: -22 to + 158°F (-30 to + 70°C) Ranges may vary with battery shelf life.				
Relative Humidity	5% to 95% non-condensing				
Ambient Light	0 - 110,000 lux				
Battery Type	Two AAA NiMH rechargeable batteries			One Lithium ion rechargeable battery	
Battery Life	~14 hours or 15,000 scans per charge			~10 hours or 5,000 scans per charge	
Scanner type	Imager (1D)		Laser (1D)	Omni-Directional Imager (2D)	
Scan Barcodes on Device Screens	✓	✓		✓	✓
Direct Part Marking (DPM) Support	✓	✓	✓	✓	✓
Vibrate Mode for Good Scans	✓	✓	✓	✓	✓
Symbologies Decoded	Bookland EAN (ISBN / EAN-13), Chinese 2 of 5, Codabar, Code 11, Code 128, Code 39, Code 93, Discrete 2 of 5, GS1 DataBar (RSS), GS1-128 (UCC-128/EAN-128), Interleaved 2 of 5 (ITF-14), MSI, Plessey, UPC/EAN, UPC/EAN/JAN supplemental redundancy, Coupon Report, ISSN EAN, Inverse 1D, ISBT concatenations, Matrix 2 of 5		Bookland EAN (ISBN / EAN-13), Chinese 2 of 5, Codabar, Code 11, Code 128, Code 39, Code 93, Discrete 2 of 5, GS1 DataBar (RSS), GS1-128 (UCC-128/EAN-128), Interleaved 2 of 5 (ITF-14), MSI, Plessey, UPC/EAN	1D: Bookland EAN (ISBN / EAN-13), Codabar (including ISBT 128 bit concatenation), Code 11, Code 128, Code 39, Code 93, Discrete 2 of 5, GS1 DataBar (RSS), GS1-128 (UCC-128/EAN-128), Interleaved 2 of 5 (ITF-14), MSI, Plessey, UPC/EAN 2D: Aztec, Codablock, Data Matrix, GS1 (EAN.UCC), Matrix 2 of 5, Maxicode, PDF 417, Macro PDF 417, Micro PDF 417, QR Code, Standard 2 of 5, Telepen, TLCode 39 Postal: Australia Post, BPO 4, Canada Post, Dutch Post (KIX), Japan Post, Planet, Postnet, RM4SCC, Sweden Post, TLCode 39, 4 State Code, USPS Intelligent Mail	
Scan Repetition Rate	5 scans/sec		5 scans/sec bi-directional	Omni-Directional / Auto-Adaptive 5 images / second	
Optical Resolution	5 mil minimum		0.004 in. (0.102mm) min./barcode element width	752(H) x 480(V) pixels, 256 gray levels	
Print Contrast	Minimum 20%		Minimum 25% MRD at 650 nm	Down to 25%	
Scan Angle	53.3° ± 3°		Wide (default): 47° ± 3° Narrow: 35° ± 3°	Horizontal: 38.9° Vertical: 25.4°	
Decode Distance ³	5.7 to 50.8 cm (2.25 to 20 in.)		3.8 to 114+ cm (1.5 to 45+ in.)	4.8 to 40.6 cm (1.9 to 16 in.) Depends on symbol size, symbology, label media, W-N ratio, scan angle.	
Bluetooth Profile Support	Human Interface Device (HID) and Serial Port Profile (SPP) Some OS versions or smartphone/tablet models support only one profile.				
Bluetooth Version	Bluetooth 2.1 + EDR (Enhanced Data Rates) with 56 bit data encryption				
Radio Range	Up to 100 m (330 ft), depending on environment, range limit is usually due to the Master Device (Phone, Tablet or Notebook)				
OS Support					
Apple iOS	✓	✓	✓	✓	✓
Android OS	✓	✓	✓	✓	✓
Windows 8, 7, Vista, XP	✓	✓	✓	✓	✓
Windows Embedded Handheld, Mobile	✓	✓	✓	✓	✓
Mac OS (HID only)	✓	✓	✓	✓	✓
SocketScan™ 10 Software	Keyboard wedge software featuring Socket EZ Pair for Android, BlackBerry, Windows. Scanner Settings configuration utility also included.				
SocketScan 10 SDK	For Apple iOS, Android, Windows. Available to members of Socket Mobile Developer Program (\$19.95/year) http://developer.socketmobile.com				
Included Items	CHS barcode scanner, AAA NiMH rechargeable batteries (2), USB AC charger kit, lanyard/belt clip with retractable tether, software			CHS barcode scanner, rechargeable battery (pre-installed), USB AC charger kit, Lanyard Software	
Warranty	Scanner: One year Accessories: 90 days				
SocketCare Extended Warranty	Sold separately. SocketCare Plus 2 Year - SKU# SC1804-1349 SocketCare Plus 3 Year - SKU# SC1805-1350 http://www.socketcare.com/				
Charging Cradle	SKU# AC4055-1382	SKU# AC4056-1383	SKU# AC4055-1382	SKU# AC4055-1382	SKU# AC4056-1383
DC Power Supply (Car Charger)	SKU# AC4057-1384				
Battery Replacement Kit:	Two AAA NiMH Rechargeable Batteries			SKU# AC4059-1479	
Electrical Safety / Environmental	Certified to IEC 60950-1, UL 60950-1, CAN/CSA C22.2 Environmental: RoHS				
EMI / RFI	FCC Part 15 Class C, RSS 210, iCES 003, C-Tick, CISPR 22, CE EN55022, EN55024, TELEC				
Laser / LED Safety	IEC 60825-1, EN 60825-1				

¹Temperature ranges may vary with battery shelf life. ²Battery life may vary with vibrate settings and work environment. ³Depends on symbol size, symbology, label media, W-N ratio, scan angle.

sales@socketmobile.com

UK/Ireland/South Africa: +44 7787 112109

France: +33 970 462 241

Toll-Free:

Switzerland:

Germany:

+1 800 552 3300 (USA/Canada)

+41 62 834 07 80

+49 9401 5299 052

EMEA & Russia: +41 62 834 0780

Asia Pacific: +1 510 933 3122

Latin America: +1 510 933 3153